



AKJ/Nalco Water DustFoam™ program helps coal company control dust, ship drier coal and save money

AKJ

NALCO Water
An Ecolab Company

CASE STUDY - MINING

CH-451



PROBLEM

A coal company was experiencing Btu's penalties placed on them because of high moisture during winter months. They were using a 2,000 tons per hour high impact crusher to crush strip coal. During the winter, the moisture levels would rise, resulting in heavy Btu penalties and a reduction of actual shippable Btu's per ton.

PROGRAM

AKJ/Nalco Water proposed and installed a DustFoam system. The dust and the moisture level of the strip coal was reduced using only 20% of the water previously applied. Total water consumption was decreased from ~100 gpm (378 lpm) utilizing water sprays to a mere 20 gpm (75 lpm) using the DustFoam foaming agent.

SUMMARY

The moisture reduction of 63% translated into a significant net weekly Btu savings. Ask your AKJ/Nalco Water sales engineer to show you what DustFoam can do for you.

CONCLUSIONS

Controlling dust may:

- Help avoid citations
- Improve morale
- Reduce cleanup costs
- Provide a safer work environment to employees
- Help facilitate PM10/PM2.5 compliance
- Reduce moisture
- Increase profit and production
- Improve relations with neighbors and reduce future perimeter expansion friction

RETURN ON INVESTMENT VALUE ADDED

Coal crushing rate = 2,000 tons per hour

Coal shipped per year = 2,000,000 tons per year

Moisture added before foaming agent = 100 gpm (378 lpm) or 1.25%

Moisture added using foaming agent = 20 gpm (75 lpm) or 0.25%

Savings: 1% Reduction in total "as shipped" moisture x the coal revenue per ton

RETURN ON INVESTMENT CALCULATION BASICS

1 Therm = 100,000 Btu's

1 Btu is required to raise 1 pound of water by 1 degree Fahrenheit

Heat of vaporization of water is 970 Btu per pound of water

To raise 1 pound (0.45 kg) water from 70°F (21°C) to vapor consumes ~1,112 Btu's

To raise 1 gallon (3.78 kg) water from 70°F (21°C) to vapor consumes ~9,275 Btu's

Before foam:

To evaporate 3,000 gph (11,356 lph) of water requires 27,825,000 Btu's per hour
(3,000 x 9,275)

Water evaporation Btu cost: (27,825,000 + 100,000 Btu's x current cost of fuel)

Using foam:

To evaporate 720 gph (2725 lph) of water requires 6,678,000 Btu's per hour (720 x 9,275)

Water evaporation Btu cost: (6,678,000 + 100,000 Btu's x current cost of fuel)



Nalco Water, an Ecolab Company

North America: 1601 West Diehl Road • Naperville, Illinois 60563 • USA

Europe: Richtstrasse 7 • 8304 Wallisellen • Switzerland

Asia Pacific: 2 International Business Park • #02-20 The Strategy Tower 2 • Singapore 609930

Greater China: 18G • Lane 168 • Da Du He Road • Shanghai China • 200062

Latin America: Av. Francisco Matarazzo • nº 1350 • Sao Paulo – SP Brazil • CEP: 05001-100

ecolab.com/nalco-water

DustFoam, Ecolab, Nalco Water and the logos are Trademarks of Ecolab USA Inc.
©2000, 2015, 2018 Ecolab USA Inc. All Rights Reserved 04/18 CH-451

NALCO Water
An Ecolab Company